

Basicmagmix



OVAN heated magnetic stirrer

- Stirring speed controlled by microprocessor.
- Stirring speed adjustable from 300 to 1.500 rpm at 10 levels.
- Temperature controlled by microprocessor.
- Temperature adjustable at OFF, 37°, 50°, 75°, 100°, 150°, 200°, 250°, 300° C and MAX.
- Heating resistance of 500 W.
- Stirring power equivalent to 5 L.
- External contact thermometer or digital control connection according to DIN
- LED's Display that shows rpm and temperature settings.
- Membrane push-button control.

- Stainless steel removable cover of 154 mm Ø.

Dimensions: 21 x 27 x 10 cm Weight: 2,3 Kg

Ref: 10000-00002 Heated magnetic stirrer Basicmagmix

Accessories

Contact thermometer of 100° C.

Ref: 20000-00037




Contact thermometer of 150° C.

Ref: 20000-00038



Contact thermometer cable


Ref: 20000-00088



Support rod


Includes 2 fastening wing nuts to fix it.
450 mm. long.

Ref: 20000-00036



PT 100 clamp or contact thermometer

Ref: 20000-00035




Set of 18 assorted magnets

Ref: 20000-00026



Kjeldhal adapter of 250 cc.

Ref: 20000-00032



Kjeldhal adapter of 500 cc.

Ref: 20000-00033